# TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

### 5-Port USB Charging Station with Built-In Device Storage, 12V 4A (48W) USB Charger Output

#### MODEL NUMBER: U280-005-ST



Charges and organizes up to 5 electronic devices at the same time. Storage compartment neatly organizes your excess cabling to reduce clutter when charging, and stores it out of the way when not in use. Recommended for quick-charging and storing tablets, smartphones and other mobile devices.

#### Description

Whether you're at home or in the office, the U280-005-ST 5-Port USB Charging Station provides enough ports and power to keep your devices at 100% capacity. No more peering behind furniture to find an available outlet or unplugging one device to charge another. You can charge up to five tablets, smartphones and other devices at the same time. The U280-005-ST doesn't require a computer, so you can take it anywhere AC power is available.

The U280-005-ST features five USB-A ports, each capable of delivering up to 5V 2.4A, which is enough for charging even battery-intensive devices. In addition, this charging station doubles as a storage unit by providing space to neatly organize cabling while your devices charge. When not in use, cables can be stored in the compartment and kept out of the way. The included adjustable brackets accommodate the number and size of the devices being charged.

To charge your USB devices, simply connect the five-foot power cord's NEMA 1-15P plug to an AC power outlet, and connect your devices to the available USB ports. The unit protects against overheating, overcurrent and overcharging—in fact, it stops charging as soon as your devices' batteries are at full capacity. Also, each port complies with USB Battery Charging (BC) specification v1.2. The brackets and power supply store conveniently in the charging station when not in use.

#### Features

**Charges Up to 5 Devices at the Same Time**Recommended for charging tablets, smartphones and other devices at home or workFunctions anywhere AC power is available—no computer required

**Provides Plenty of Juice for Charging**Delivers up to 5V, 2.4A per port—enough for charging batteryintensive devices like the Apple iPadProtects against overheating, overcurrent and overchargingComplies with USB Battery Charging (BC) specification v1.2

Efficiently Stores Your Cables / Devices Too7 adjustable brackets provide space to neatly organize devices as they chargeConvenient storage compartment lets you neatly organize your cabling while your devices chargeWhen not in use, cables can be stored in the compartment and kept out of the way

Easy to UseExternal dual-voltage power supply with C8 power inlet and detachable C7 to 1-15P 5 ft. cordNo computer required

#### Highlights

- 5V, 2.4A per port for charging battery-intensive devices
- All five ports support USB Battery Charging (BC) specification v1.2
- 7 adjustable storage brackets for organizing devices
- Storage compartment neatly organizes your cabling
- External dual-voltage power supply with NEMA 1-15P plug
- Protects against overheating, overcurrent and overcharging

#### **Package Includes**

- U280-005-ST 5-Port USB Charging Station
- (7) Storage brackets
- External power supply (Input: 100–240V, 50/60 Hz, 1.5A; Output: 12V, 4A)
- C7 to NEMA 1-15P power cord, 5 ft.
- Quick Start Guide



### Specifications

| OVERVIEW                                     |   |
|--|---|
| UPC Code                                     | 037332199584  |
| Product Type                                 | Charging Station                                    |
| Charging Form Factor                         | Charging Hub  |
| Device Compatibility                         | Phone; Tablet; Amazon Kindle                        |
| INPUT  |   |
| AC Power Adapter Plug(s)                     | NEMA 1-15P North America                            |
| AC Power Adapter Input Specs (V /<br>Hz / A) | 100-240V / 50/60Hz / 1.5A                           |
| AC Power Adapter Output Specs (V / A)        | 12V / 4A  |
| AC Power Adapter Cord Length (m)             | 1   |
| Nominal Input Voltage(s) Supported           | 120V AC; 230V AC                                    |
| Voltage Compatibility (VAC)                  | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240    |
| Input Plug Type                              | NEMA 1-15P (NON-POLARIZED)                          |
| OUTPUT                                       |   |
| Overload Protection                          | Yes   |
| POWER  |   |
| Power Source Type                            | AC Adapter  |
| AC Adapter                                   | Input: 100-240V, 50/60Hz, 1.5A; Output: 12V, 4A     |
| DC Barrel Plug                               | OD: 5.5 x 2.5 x 10mm, Positive Pin, Negative Sleeve |
| Power Consumption (Watts)                    | 12.7  |
| Power Consumption Detail                     | 12.7W (Operating) 0.23W (Standby)                   |
| USER INTERFACE, ALERTS & CONTROLS            |   |
| LED Indicators                               | Blue (Power)  |
| CHARGING                                     |   |
| Number of Charging Ports                     | 5   |
| Total Charging Amps                          | 4A  |
| Total Charging Watts                         | 48  |
| Charging Method                              | USB   |
| Charging Method Detail                       | 5V - 1.5A (7W)                                      |

# TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

| Charging Port Type                   | (5) USB A (FEMALE)                    |
|--------------------------------------|---------------------------------------|
| Charging Ports Details               | USB-A: 12V/4A                         |
| Charging Ports / Amps                | (5) 2.4A                              |
|                                      |                                       |
| PHYSICAL                             |                                       |
| Color                                | Black                                 |
| Material of Construction             | Polycarbonate                         |
| Shipping Dimensions (hwd / in.)      | 2.70 x 6.00 x 10.10                   |
| Shipping Dimensions (hwd / cm)       | 6.86 x 15.24 x 25.65                  |
| Shipping Weight (Ibs.)               | 2.05                                  |
| Shipping Weight (kg)                 | 0.93                                  |
| Unit Dimensions (hwd / in.)          | 0.787 x 6.614 x 4.882                 |
| Unit Dimensions (hwd / cm)           | 2 x 16.8 x 12.4                       |
| Unit Packaging Type                  | Box                                   |
| Unit Weight (Ibs.)                   | 1.3                                   |
| Unit Weight (kg)                     | 0.59                                  |
|                                      |                                       |
| ENVIRONMENTAL                        |                                       |
| Operating Temperature Range          | 41° to 95°F (5° to 35°C)              |
| Storage Temperature Range            | -4° to 122°F (-20° to 50°C)           |
| Relative Humidity                    | 20% to 80% RH, Non-Condensing         |
| CONNECTIONS                          |                                       |
| Number of Ports                      | 5                                     |
| Side A - Connector 1                 | NEMA 1-15P (NON-POLARIZED)            |
| Side B - Connector 1                 | (5) USB A (FEMALE)                    |
|                                      |                                       |
| FEATURES & SPECIFICATIONS            |                                       |
| GaN Technology                       | No                                    |
| Overcurrent Protection               | Yes                                   |
| Overvoltage Protection               | Yes                                   |
| IP68 Rated                           | No                                    |
| IP20 Rated                           | No                                    |
| STANDARDS & COMPLIANCE               |                                       |
| External Power Supply Certifications | CCC; FCC; GS; PSE; RoHS; TUV; UL; cUL |
|                                      |                                       |



1000 Eaton Boulevard Cleveland, OH 44122 United States

#### WARRANTY & SUPPORT

Product Warranty Period (Worldwide)

2-year limited warranty



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.