

High-Speed HDMI Cable, Digital Video with Audio, UHD 4K (M/M), Black, 3 ft. (0.91 m)

MODEL NUMBER: P568-003











Highlights

- Premium double-shielded digital audio/video cable
- Supports iPad2 Video Mirroring when used with Apple Digital AV Adapter
- Gold-plated connectors provide optimal signal transfer
- High Speed HDMI and HDCP compliant
- Supports Ultra High Definition (UHD) 4K video resolutions

Package Includes

3-ft. (0.91 m) High Speed HDMI Gold Cable

Description

This High Speed HDMI Gold Cable allows interconnection between digital display devices, such as HDTVs and projectors, to digital source devices, such as satellite boxes, Blu-Ray players and AV receivers. Supports iPad2 Video Mirroring when used with Apple Digital AV Adapter. HDMI assures that the best audio/video signal is always sent from the source to the display by allowing uncompressed video and multi-channel audio data to be input to the display device through one single cable. An HDMI connection allows input at high rates of speed, up to 18 Gbps.

Features

- Creates a pure digital connection between HDMI-enabled HDTV display devices and HDMI-enabled digital video sources
- Supports iPad2 Video Mirroring when used with Apple Digital AV Adapter
- Gold-plated connectors provide optimal signal transfer
- Premium double-shielded cable protects against outside noise (EMI/RFI)
- Impedance-matched twisted-pair construction reduces cross-talk and interference
- Perfect for connecting an iPad2 to an HDTV (video mirroring) to watch movies, play games, surf the web and display presentations
- Supports Ultra High Definition (UHD) 4K video resolutions

Specifications

OVERVIEW		
UPC Code	037332160911	
Product Type	Passive Cable	
Technology	HDMI	
Cable Type	Passive	



Max Supported Video Resolution 3840 x 2160 (4K) @ 30Hz Max Supported Color Depth 48-bit Deep Color HDR Support No 3D Video Supported Yes Croman Sub Sampling 4:4:4 EDID Support Yes Signal Transmission Bidirectional AUDIO AUDIO AUDIO AUDIO AUDIO Specification ARC USER INTERFACE, ALERTS & CONTROLS LED Indicators 0 PPHYSIGAL Color Black Material of Construction PVC Cable Jacket Color Black Connector Color Black Connector Color Black Connector Color Black Contector Delianeter (OD) Sub Jacket Rating VW-1 Cable Length (ft.) 3 Cable Length (ft.) 3 Cable Length (ft.) 3 Salping Dimensions (hwd / cm) 2.311 x 17.53 x 0.25 Shipping Dimensions (hwd / cm) 2.311 x 17.53 x 0.25 Shipping Weight (kg) 0.08 ENVIRONMENTAL				
Max Supported Color Depth	VIDEO			
### READ Support ### AU A A A A A A A A A A A A A A A A A	Max Supported Video Resolution	3840 x 2160 (4K) @ 30Hz		
Side Supported Yes Chroma Sub Sampling 4:4:4 EDID Support Yes Signal Transmission Bidirectional AUDIO Audio Specification ARC USER INTERFACE, ALERTS & CONTOLS LED Indicators 0 PHYSICAL Catelia Jackett Color Black Consector Color Black Consector Color Black Cable Jackett Rating WW-1 Cable Jacket Rating WW-1 Cable Length (m) 0.91 Cable Length (m) 0.91 Cable Length (m) 36 Ferrite Orie No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 2.11 x 17.53 x 0.25 Shipping Weight (lgs) 0.08 ENVIRONMENTAL	Max Supported Color Depth	48-bit Deep Color		
Chroma Sub Sampling 4:4-4 EDID Support Yes Signal Transmission Bidirectional AUDIO AUDIO AUDIO Specification ARC USER INTERFACE, ALERTS & CONTROLS LED Indicators 0 PHYSICAL Color Black Material of Construction PVC Cable Jacket Color Black Connector Color Black Cable Jacket Material PVC Cable Length (n) 30 Cable Length (n) 3.3 Cable Length (m) 0.91 Cable Length (m) 3.6 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / orm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (ltg.) 0.08 ENVIRONMENTAL	HDR Support	No		
EDID Support Yes Signal Transmission Bidirectional AUDIO AUGIO Specification ARC USER INTERFACE, ALERTS & CONTROLS LED Indicators 0 PHYSICAL Color Black Material of Construction PVC Cable Jacket Color Black Connector Color Black Cable Jacket Material PVC Cable Jacket Material PVC Cable Jacket Material PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (It) 3 Cable Length (In) 0.91 Cable Length (In) 0.91 Cable Length (In) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (Itwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (Itwd / orn) 23.11 x 17.53 x 0.25 Shipping Weight (Ibs) 0.08 ENVIRONMENTAL	3D Video Supported	Yes		
Signal Transmission Bidirectional AUDIO Audio Specification ARC USER INTERFACE, ALERTS & CONTROLS LED Indicators 0 PHYSICAL Color Black Material of Construction PVC Cable Jacket Color Black Connector Color Black Cable Jacket Material PVC Cable Jacket Material PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Length (m) 30 Gable Length (m) 0.91 Cable Length (m) 0.91 Cable Length (m) 0.91 Cable Length (m) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (thwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (thwd / orn) 23.11 x 17.53 x 0.25 Shipping Weight (tbs.) 0.17 Shipping Weight (kg) 0.08	Chroma Sub Sampling	4:4:4		
Audio Specification ARC USER INTERFACE, ALERTS & CONTROLS LED Indicators 0 PHYSICAL Color Black Material of Construction PVC Cable Jacket Color Black Connector Color Black Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (m) 0.91 Cable Length (m.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 2.11 x 17.53 x 0.25 Shipping Weight (kg) 0.08 EENVIRONMENTAL	EDID Support	Yes		
Audio Specification ARC USER INTERFACE, ALERTS & CONTROLS LED Indicators 0 PHYSICAL Color Black Material of Construction PVC Cable Jacket Color Black Connector Color Black Cable Jacket Material PVC Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating INF Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (ft.) 36 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / om) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08 ENVIRONMENTAL	Signal Transmission	Bidirectional		
USER INTERFACE, ALERTS & CONTROLS LED Indicators 0 PHYSICAL Color Black Material of Construction PVC Cable Jacket Color Black Connector Color Black Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Jacket Rating VW-1 Cable Jacket Rating Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	AUDIO	AUDIO		
PHYSICAL	Audio Specification	ARC		
PHYSICAL	USER INTERFACE, ALERTS & CONTROLS			
Color Black Material of Construction PVC Cable Jacket Color Black Connector Color Black Cable Jacket Material PVC Cable Jacket Rating WW-1 Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	LED Indicators			
Color Black Material of Construction PVC Cable Jacket Color Black Connector Color Black Cable Jacket Material PVC Cable Jacket Rating WW-1 Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08				
Material of Construction PVC Cable Jacket Color Black Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	PHYSICAL			
Cable Jacket Color Black Connector Color Black Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Color	Black		
Connector Color Black Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Material of Construction	PVC		
Cable Jacket Material PVC Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Cable Jacket Color	Black		
Cable Jacket Rating VW-1 Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Connector Color	Black		
Cable Outer Diameter (OD) 6.0 mm Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Cable Jacket Material	PVC		
Wire Gauge (AWG) 30 Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Cable Jacket Rating	VW-1		
Cable Length (ft.) 3 Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Cable Outer Diameter (OD)	6.0 mm		
Cable Length (m) 0.91 Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Wire Gauge (AWG)	30		
Cable Length (in.) 36 Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) ENVIRONMENTAL	Cable Length (ft.)	3		
Ferrite Core No Minimum Bend Radius 30mm Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Cable Length (m)	0.91		
Minimum Bend Radius Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) ENVIRONMENTAL	Cable Length (in.)	36		
Shipping Dimensions (hwd / in.) 9.10 x 6.90 x 0.10 Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08	Ferrite Core	No		
Shipping Dimensions (hwd / cm) 23.11 x 17.53 x 0.25 Shipping Weight (lbs.) 0.17 Shipping Weight (kg) 0.08 ENVIRONMENTAL	Minimum Bend Radius	30mm		
Shipping Weight (lbs.) Shipping Weight (kg) 0.08 ENVIRONMENTAL	Shipping Dimensions (hwd / in.)	9.10 x 6.90 x 0.10		
Shipping Weight (kg) 0.08 ENVIRONMENTAL	Shipping Dimensions (hwd / cm)	23.11 x 17.53 x 0.25		
ENVIRONMENTAL	Shipping Weight (lbs.)	0.17		
	Shipping Weight (kg)	0.08		
	ENVIRONMENTAL			
Operating Temperature Range 14° to 122°F (-10° to 50°C)	Operating Temperature Range	14° to 122°F (-10° to 50°C)		



Storage Temperature Range	5° to 140°F (-15° to 60°C)
Operating Humidity Range	0% to 90% RH, Non-Condensing
Storage Humidity Range	0% to 90% RH, Non-Condensing
COMMUNICATIONS	
EDID Compatible	Yes
Consumer Electronics Control (CEC) Supported	Yes
CONNECTIONS	
Side A - Connector 1	HDMI (MALE)
Side B - Connector 1	HDMI (MALE)
Connector Plating	Gold
Contact Plating	Gold
Connector Style	Straight
Latching or Gripping Connector	No
FEATURES & SPECIFICATIONS	
EMI/RFI Line Noise Protection	No
MST Support	No
Antibacterial	No
IP68 Rated	No
IP20 Rated	No
Armored Cable	No
Ethernet Support	No
HDCP Specification	1.4; 2.2
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; REACH
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty







© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.