Specifications





Photo is representative





Eaton 5SC1500I

Eaton 5SC UPS, 1500 VA, 1050 W, Input: C14, Outputs: (8) C13, Tower

| General specifications | |
|-------------------------|--|
| PRODUCT NAME | Eaton 5SC UPS |
| CATALOG NUMBER | 5SC1500I |
| UPC | 743172045171 |
| PRODUCT LENGTH/DEPTH | 410 mm |
| PRODUCT HEIGHT | 210 mm |
| PRODUCT WIDTH | 150 mm |
| PRODUCT WEIGHT | 15.2 kg |
| WARRANTY | 2 year |
| COMPLIANCES | CE Marked TUV |
| CERTIFICATIONS | IEC/EN 62040-1 UL 1778 IEC/EN 62040-2 CE EAC cTUVus |



| Additional specifications | |
|----------------------------|--|
| CONSTRUCTION TYPE | Free standing model |
| ENCLOSURE | Black |
| PACKAGE CONTENTS | USB cableSerial cable(2) IEC-IEC cablesQuickstart guideSafety instructions |
| PHASE (OUTPUT) | 1 |
| AUTO SHUTDOWN FUNCTION | Yes |
| COLOR | Black |
| EFFICIENCY AT MAX. LOAD | 97 |
| RACK MOUNTING KIT | No |
| PHASE (INPUT) | 1 |

| Battery | |
|-----------------------------|--|
| BATTERY TYPE | Lead-acid maintenance- free (replaceable) |
| RUNTIME GRAPH | \$row.attributeValue.cdata |
| BATTERY REPLACEMENT | User replaceable |
| BATTERY QUANTITY | 3 |
| BATTERY MANAGEMENT | ABM or constant voltage charging method (user selectable), automatic battery test, deep discharge protection |
| BATTERY RATING | 12 V / 9 Ah |
| EXTENDED BATTERY CAPABILITY | No |

| Communications | |
|-------------------------------|--|
| INCLUDES NETWORK CARD | No |
| COMMUNICATION | USB port (HID compliant)Serial port (RS232) |
| ETHERNET INTERFACE | No |
| USER INTERFACE | LCD Display |
| POTENTIAL FREE SWITCH CONTACT | No |
| EXPANSION SLOTS | No |
| SOFTWARE COMPATIBILITY | Eaton Intelligent Power Protector |
| TYPE OF INTERFACE | Other |

| Electrical input | |
|--------------------------|---|
| INPUT CONNECTION | C14 |
| INPUT NOMINAL VOLTAGE | 230V default (220/230/240V) |
| NOMINAL FREQUENCY | 50-60 Hz |
| INPUT VOLTAGE RANGE | 184-276 V |
| INPUT FREQUENCY RANGE | 45-55 Hz (50 Hz system), 55-65 Hz (60 Hz system) |
| | |

| Electrical output | |
|---------------------------|--------------------------------|
| RECEPTACLE | (8) C13 |
| VOLTAGE | 230V |
| WATTAGE | 1050 W |
| OUTPUT POWER FACTOR | 0.7 |
| OUTPUT VOLTAGE RANGE | 230 V (+6%/-10%) |
| OUTPUT WAVEFORM | Sine wave |
| OUTPUT NOMINAL VOLTAGE | 230V default (220/230/240V) |
| FEED TYPE | 1 |
| TOPOLOGY | Line-interactive |
| VA RATING | 1500 VA |

| Environmental | |
|-------------------|----------------------|
| ALTITUDE | 2000 m |
| NOISE LEVEL | <40 dB at 1 meter |
| TEMPERATURE RANGE | 0-90% non-condensing |
| RELATIVE HUMIDITY | 0-90% non-condensing |
| | |

| Resources | |
|----------------------------|---|
| BROCHURES | Eaton UPS Services Quick Guide - EN |
| | Eaton 5SC UPS - 500/3000VA - Datasheet |
| | Eaton UPS and battery services - EN |
| COMPLIANCE INFORMATION | EU DoC Eaton 5SC |
| MANUALS AND USER GUIDES | Eaton 5SC UPS - 500i/750i/1000i/1500i - Installation and user manual (multiple languages) |

| PROJECT NAME: | |
|-----------------|--|
| PROJECT NUMBER: | |
| PREPARED BY: | |
| DATE: | |
| | |



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com



information.



latest product and support

Follow us on social media to get the



