

Specifications

Eaton MBP3KI



Photo is representative

Eaton HotSwap MBP maintenance bypass, 3000 VA, IEC, Input: C20, 200-240V, Outlets: (6) C13, (1) C19

General specifications

PRODUCT NAME	Eaton HotSwap MBP maintenance bypass
CATALOG NUMBER	MBP3KI
PRODUCT LENGTH/DEPTH	76.5 mm
PRODUCT HEIGHT	50 mm
PRODUCT WIDTH	439 mm
PRODUCT WEIGHT	1.9 kg
WARRANTY	2 year
COMPLIANCES	CE Marked
CERTIFICATIONS	CE
MODEL CODE	Eaton HotSwap MBP IEC

Product specifications

TYPE	Hotswap MBP
FORM FACTOR	1U
OUTLET CONTROL	No
PACKAGE CONTENTS	• Maintenance Bypass • Cable locking system • Connection cable to the UPS • Rack-mounting kit • User manual
OPERATING TEMPERATURE	0° to 40°C (32° to 104°F)
MOUNTING DIRECTION	Horizontal/vertical
COLOR	Black
INPUT CONNECTION	C20
VA RATING	3000 VA
INPUT VOLTAGE	200-240V
PHASE	Single-phase
OUTLETS	(6) C13, (1) C19
NUMBER OF OUTPUTS C13	6
NUMBER OF OUTPUTS C19	1
NUMBER OF OUTLETS WITH EARTH PIN	7
SNMP	No
ETHERNET INTERFACE	No
SERIAL INTERFACE	No
MASS CONFIGURATION	No
ELECTRICAL CONNECTION	Socket outlet
EVALUATION	Other
MOUNTING DIMENSION (METRICAL)	50
MOUNTING DIMENSION (STANDARDIZED)	482.6 mm (19 inch)
SWITCHABLE	No
OVER VOLTAGE CATEGORY	2
AMPEREMETER	No
FITTED WITH:	LED indication Mounting material
COMMUNICATION	No

Resources

BROCHURES	Eaton UPS and battery services - EN
	Eaton UPS Services Quick Guide - EN
COMPLIANCE INFORMATION	EU declaration of conformity Eaton FlexPDU and Eaton Hot-Swap MBP

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

