

Product datasheet

Specifications



APC NetShelter Basic Rack PDU,
0U, 1PH, 3.3kW, 100-240V 20A or
200-240V 16A, 13 C13 outlets,
C20 inlet

AP6020A

Overview

Presentation	Reliable rack power distribution designed to increase manageability and efficiency in the data center The output and input connections are (13) C13 Real-time remote monitoring of connected loads User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
Lead time	Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Provided equipment	Installation guide Safety guide

Complementary

Input Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Height	388 mm
Width	44 mm
Depth	93 mm
Net weight	1.5 kg
Mounting location	Front Rear
Mounting preference	Lower
Input Plug Type	IEC 60320 C20
Mounting mode	Not rack-mountable
Rack units	1U
USB compatible	No
Mounting position	Horizontal
[In] rated current	16 A
permissible voltage	100...240 V
Max line current	20 A
Input current limits	20 A

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Load capacity	3300 VA
Network frequency	50/60 Hz
Outlet type and quantity	13 IEC 60320 C13

Environment

Product certifications	cUL listed CE EAC IRAM PSE UL listed VDE
------------------------	--

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.6 cm
Package 1 Width	7.6 cm
Package 1 Length	21 cm
Package 1 Weight	2.02 kg
SCC14	10731304327803

Contractual warranty


Warranty (in months)	24
----------------------	----

Environmental Data


Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	3734
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACH Regulation	REACH Declaration
Halogen-free status	Product contains halogen above thresholds

 Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Again



 Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

