





AP7922B

_					
O١	10	r۱	/1	9	M

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	3 m
Number of cables	1
Provided equipment	Documentation CD Installation guide Rack mounting brackets

Complementary

Input Voltage	200 V	
	208 V	
	230 V	
Height	89 mm	
Width	445 mm	
Output Voltage	230 V	
Depth	114 mm	
Net weight	4.5 kg	
Mounting location	Front	
J	Rear	
	rour	
Mounting preference	No preference	
Input Plug Type	IEC 60309 32 A 2P + E	
Mounting mode	Rack-mounted	
Rack units	2U	
Mounting position	Horizontal	
permissible voltage	220240 V	
Input current limits	32 A	
Load capacity	7360 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	16 IEC 60320 C13	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Environment

Product certifications	CE GOST IRAM MIC VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3
Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	015240 m

Packing Units

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	36.8 cm
Package 1 Length	50.8 cm
Package 1 Weight	6.55 kg

Contractual warranty

Warranty (in months) 2



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Total lifecycle Carbon footprint	2191
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Energy Efficiency Optimized	Energy efficient product

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Removable battery	Yes
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product datasheet

AP7922B

Image of product / Alternate images

Alternative

