



Power Cord Kit (6 ea), Locking, C13 to C14, 1.8m

AP8706S-WW

Overview

Presentation	This Series of Rack Power Distribution Units (PDU) comes with Locking IEC Receptacles. The output and input connections are C13 to C14. The cord length is 1.8m. Locking IEC system allows the use of optional locking IEC power cords for added power cord security and enhanced reliability. No tools are required to disengage the locking feature and remove the plug from the locking receptacle.
Lead time	Usually in Stock

Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C14
Cable length	1.82 mm
Number of cables	6

Physical

Colour	Black	
Height	240 mm	
Width	75 mm	
Depth	55 mm	
Net weight	1.35 kg	
Mounting preference	No preference	
Mounting mode	Not rack-mountable	

Input

Max line current	10 A
Input current limits	10 A

Output

Max current draw	10 A
Number of power socket outlets	1 IEC 60320 C13
Power cable length	1.8 m

Conformance

Product certifications	CCC	
	PSE	
	VDE	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Environmental

Ambient air temperature for operation	070 °C
Relative humidity	2080 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2575 °C
Storage Relative Humidity	2080 %
Storage altitude	015240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	3.400 cm
Package 1 Length	6.100 cm
Package 1 Weight	1.220 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	26.000 cm
Package 2 Width	33.000 cm
Package 2 Length	56.000 cm
Package 2 Weight	12.950 kg

Contractual warranty

Warranty (in months)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Total lifecycle Carbon footprint	179
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds
[⋯] Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Longer

Ů Lifetime extension		
Repair	No	

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

AP8706S-WW

Image of product / Alternate images

Alternative

