Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Power Cord, C13 to C14, 2.5m



AP9870

Overview

Lead time Usually in Stock

Main

Product or component type	Power cord
Input Connection Type	IEC 60320 C14
Cable length	2.4 m
Number of cables	1

Physical

Colour	Black
Height	38 mm
Width	76 mm
Depth	203 mm
Net weight	0.23 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Input

Network frequency	50/60 Hz	
permissible voltage	90250 V	
Max line current	10 A	
Input current limits	10 A	

Output

Max current draw	10 A
Number of power socket outlets	1 IEC 60320 C13
Protection type	Without circuit breaker

Conformance

Product certifications	CSA
	UL listed
	VDE

Environmental

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Ambient air temperature for operation	045 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	015240 m

Packing Units

PCE
1
5.100 cm
10.200 cm
20.300 cm
295.000 g
S03
10
30 cm
30 cm
40 cm
3.370 kg
P12
80
45.000 cm
80.000 cm
120.000 cm
38.960 kg

Contractual warranty

Warranty (in months) 24



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	31
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds
[⋯] Energy efficiency	
Energy Efficiency Optimized	Energy efficient product

Use Longer

Ů Lifetime extension		
Repair	No	

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins