

Product datasheet

Specifications



APC Back-UPS, 2200VA, Tower, 230V, 4 Universal outlets, AVR

BX2200MI-MS

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V AC 1 phase
Cos phi	0.54
Input voltage limits	140...300 V
Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	1200 W
rated power in VA	2200 VA
Output connection type	4 universal
USB Charging Port	None
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1200 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Stepped approximation to a sinewave
Full load runtime	00:01:00 1200 W
Half load runtime	00:08:30 600 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains

Complementary

Battery type	Lead-acid battery
Battery voltage	24 V
Battery graph comments	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Battery life	3...5 year(s)
Battery type	Lead-acid internal included

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Control panel	LED Status display with on line : on battery
UPS connectivity	None
Surge energy rate	273 J
Cable length	1.2 m
Number of cables	1
Colour	Black
Height	190 mm
Width	140 mm
Depth	390 mm
Net weight	12.3 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting mode	Tower
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Back-UPS
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...40 °C
Storage altitude	0...3000 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	40 dBA
Operating altitude	0...3000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.7 cm
Package 1 Width	49.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	13.3 kg

SCC14	10731304410734
-------	----------------

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

[EU RoHS Directive](#)

Compliant

SCIP Number

Ec96232c-7000-4722-846e-a372cdfca8dc

REACH Regulation

[REACH Declaration](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Removable battery

User replaceable

Take-back

No

Image of product / Alternate images

Alternative

