



! To be discontinued

Usually in Stock

APC Easy Rack PDU, Metered, 1U, 1 Phase, 3.7kW, 230V, 16A, 8 x C13 outlets, IEC60320 C20 inlet

EPDU1016M

- ! Discontinued on: 6 Jun 2025
- ! To be end-of-service on: 31 Dec 2025

Overview

Lead time

Main	
Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	2.49 m
Provided equipment	Horizontal mounting brackets Installation guide User manual Cable

## Complementary

Jompiomontal y	
Input Voltage	200 V
	208 V
	230 V
Height	44.4 mm
Width	482 mm
Output Voltage	208 V
	230 V
Depth	44 mm
Net weight	0.7 kg
Mounting location	Front
	Rear
Mounting preference	No preference
Input Plug Type	IEC 60320 C20
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Outlet type and quantity	8 IEC 60320 C13

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

# **Environment**

Product certifications	CE TÜV
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	015240 m

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	15 cm
Package 1 Length	56 cm
Package 1 Weight	1.4 kg

# **Contractual warranty**

Warranty (in months)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint		
Total lifecycle Carbon footprint	914	

### **Use Better**

<b>⊗</b> Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	780cb2d6-f852-4c3c-987f-e705629194ca
REACh Regulation	REACh Declaration
Energy Efficiency Optimized	Energy efficient product

## **Use Again**

○ Repack and remanufacture		
End of life manual availability	End of Life Information	
Take-back	No	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	