

! To be discontinued

APC Easy Rack PDU, Basic, 0U, 1 Phase, 3.7kW, 230V, 16A, 20 x C13 and 4 x C19 outlets, IEC60309 2P+E inlet

EPDU1116B

- ! Discontinued on: 1 Dec 2025
- ! To be end-of-service on: 30 Sep 2028

Overview

Lead time Usually in Stock

Main

····		
Colour	Black	
Product or component type	PDU	
PDU type	Basic	
Cord length	2.99 m	
Number of cables	1	
Provided equipment	Installation guide Toolless mounting kit Vertical mounting brackets	

Complementary

-		
Input Voltage	200 V 208 V 230 V	
Height	902 mm	
Width	62 mm	
Output Voltage	230 V	
Depth	44.4 mm	
Net weight	2.2 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 16 A 2P + E	
Mounting mode	Rack-mounted	
Rack units	OU	
Mounting position	Vertical	
Input current limits	16 A	
Load capacity	3680 VA	
Network frequency	50/60 Hz	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Environment

Product certifications	CE TÜV
Ambient air temperature for operation	045 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	015240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	132 cm
Package 1 Width	11 cm
Package 1 Length	16 cm
Package 1 Weight	2.98 kg

Contractual warranty

Warranty (in months)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint	
Total lifecycle Carbon footprint	56
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances		
Packaging made with recycled cardboard	No	
Packaging without single use plastic	No	
EU RoHS Directive	Compliant	
REACh Regulation	REACh Declaration	
[™] Energy efficiency		
Energy Efficiency Optimized	Energy efficient product	

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins