

Product datasheet

Specifications



APC Easy UPS On-Line SRV 240V Battery Pack for 6/10KVA Extended Runtime Model

SRV240BP-9A

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	External battery pack
Battery type	Lead-acid battery
Provided equipment	User manual Battery cable
Range of product	Easy UPS On-Line

Batteries & Runtime

Number of battery blocks per string	20
Device mounting	Floor mounted
Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	240 V

Physical

Colour	Black
Height	368 mm
Width	190 mm
Depth	485 mm
Net weight	60 kg
Mounting mode	Not rack-mountable
USB compatible	No

Conformance

Product certifications	CE UKCA EAC EN/IEC 62040-1
------------------------	-------------------------------------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	60.000 cm
Package 1 Width	80.000 cm
Package 1 Length	60.000 cm
Package 1 Weight	67.999 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	288 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	233 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	16 kg CO2 eq.
Carbon footprint of the installation phase [A5]	18 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	237 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	22 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	5ac12844-46eb-471b-94f1-318e06a714a6
REACH Regulation	REACH Declaration

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture


End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

