

# Product datasheet

Specifications



## APC Easy Metered Rack PDU, 1U, 16A, 230V, 8 C13 outlets

EPDU2016M

### Overview

Lead time Usually in Stock

### Main

Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	2.49 m
Provided equipment	Horizontal mounting brackets

### Complementary

Input Voltage	230 V 1 phase
Height	44 mm
Width	482 mm
Output Voltage	208 V
Depth	100 mm
Net weight	1.7 kg
Mounting location	Front
Mounting preference	No preference
Input Plug Type	IEC 60320 C20
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Outlet type and quantity	8 IEC 60320 C13

### Environment

Product certifications	CE UKCA
Ambient air temperature for operation	-5...50 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

---

Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %

---

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.8 cm
Package 1 Width	21 cm
Package 1 Length	57 cm
Package 1 Weight	3 kg

---

## Contractual warranty

---

Warranty (in months)	12
----------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	649 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Carbon footprint of the manufacturing phase [A1 to A3]	33 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	6 kg CO2 eq.
Carbon footprint of the installation phase [A5]	2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	603 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	5 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	44
End of life manual availability	<a href="#">End of Life Information</a>
Removable battery	No
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

