

Product datasheet

Specifications



APC Smart-UPS X, Line Interactive, 1500VA, Rack/tower convertible 2U, 230V, 8x C13 IEC, SmartSlot, Extended runtime

SMX1500RM12U

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage 230 V AC 1 phase

Input Connection Type IEC 320 C14

Switching current capacity 10 A

Input voltage limits 151...302 V adjustable
160...286 V

Network frequency 50/60 Hz +/- 3 Hz auto-sensing

Output voltage 230 V AC 1 phase

Rated power in W 1200 W

rated power in VA 1500 VA

Output connection type 8 IEC 320 C13
2 IEC Jumpers

Harmonic distortion Less than 5 %

Maximum configurable power in VA 1500 VA

Maximum configurable power in W 1200 W

UPS type Line interactive

Wave type Sine wave

Output frequency 50/60 Hz +/- 3 Hz sync to mains

Complementary

Battery type Lead-acid internal included

Control panel Multifunction LCD status and control console

Emergency power off Yes

Free slots 1

Alarm Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

UPS connectivity Serial port
USB port
Available expansion slot

Surge energy rate 645 J

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Number of rack unit	2U
Cable length	1.8 m
Number of cables	1
Colour	Black
Height	89 mm
Width	432 mm
Depth	490 mm
Net weight	24.82 kg
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting mode	Rack-mounted with included kit
Provided equipment	CD with software Documentation CD Installation guide Rack mounting support rails Removable support feet Smart UPS signalling RS-232 cable USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	Extended run
Redundant	No
Range of product	Smart-UPS
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE CSA EAC RCM UK PSTI
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...45 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %
Acoustic level	40 dBA
Heat dissipation	133 Btu/h
Operating altitude	0...10000 ft

Batteries & Runtime

Run Time	View Runtime Graph 
Efficiency	View Efficiency Graph 
Battery type	Lead-acid battery
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	APCRBC115 
Battery charger power	103 W rated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.600 cm
Package 1 Width	58.900 cm
Package 1 Length	62.000 cm
Package 1 Weight	30.000 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	16
Package 2 Height	133.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	524.000 kg

Contractual warranty

Warranty (in months)	36 UPS 24 Battery
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 249 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	787 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	19 kg CO2 eq.
Carbon footprint of the installation phase [A5]	5 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	408 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	29 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold



Energy efficiency

Energy Efficiency Optimized	Energy efficient product
-----------------------------	--------------------------

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	51
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



