

Product datasheet

Specifications



APC Smart-UPS SRT 72V 2.2kVA RM Battery Pack



SRT72RMBP

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	External battery pack
Number of rack unit	2U
Battery type	Lead-acid battery
Provided equipment	Documentation CD Installation guide Rack mounting brackets
Range of product	Smart-UPS Battery Systems

Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	0
Battery voltage	72 V
Number of battery replacement quantity	2
Replacement battery	APCRBC141

Physical

Colour	Black
Height	85 mm
Width	432 mm
Depth	594 mm
Net weight	33.9 kg
Mounting mode	Rack-mounted

Output

Battery capacity	20 Ah
------------------	-------

Conformance

Standards	OSHPD
-----------	-------

Environmental

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
Storage Relative Humidity	0...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.900 cm
Package 1 Width	59.900 cm
Package 1 Length	83.100 cm
Package 1 Weight	40.820 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	2
Package 2 Height	100.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	93.640 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	187 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	151 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	10 kg CO2 eq.
Carbon footprint of the installation phase [A5]	11 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	142 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	14 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	5ac12844-46eb-471b-94f1-318e06a714a6
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	48
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No

Image of product / Alternate images

Alternative

