

Product datasheet

Specifications



APC Smart-UPS RT Battery Pack 192V, rackmount, 4U, wo rail kit

SRTG192XLBP2

Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

Main

Product or component type	External battery pack
Number of rack unit	4U
Battery type	Lead-acid battery
Provided equipment	Installation guide Warranty card
Range of product	Smart-UPS Battery Systems

Batteries & Runtime

Device mounting	Stand alone battery stack Rack mount
Number of battery filled slots	4
Number of battery free slots	0
Number of battery replacement quantity	2
Battery voltage	192 V
Replacement battery	APCRBC172

Physical

Colour	Black
Height	175 mm
Width	440 mm
Depth	700 mm
Net weight	116 kg
Mounting mode	Rack-mounted
USB compatible	No

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...6600 ft
Storage Relative Humidity	0...95 % non-condensing

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage altitude	0...15240 m
------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.5 cm
Package 1 Width	79 cm
Package 1 Length	59 cm
Package 1 Weight	122.4 kg

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	560 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	453 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	30 kg CO2 eq.
Carbon footprint of the installation phase [A5]	34 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	427 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	43 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	488c31fb-3af8-42cf-9558-1362d000a07e
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	48
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



