

Product datasheet

Specifications



RACK PDU, BASIC, HALF HEIGHT, 100-240V/20A, 220-240V/16A, (14) C13

AP6003A

Overview

Lead time Usually in Stock

Main

Colour Black

Product or component type PDU

PDU type Basic

Provided equipment Installation guide
Safety guide

Complementary

Input Voltage 230 V

Height 523 mm

Width 56 mm

Output Voltage 100 V
120 V
200 V
208 V
230 V
240 V

Depth 47 mm

Product weight 1.88 kg

Mounting location Side

Mounting preference Lower

Input Plug Type IEC 60320 C20

Mounting mode Not rack-mountable

Rack units 0U

USB compatible No

Mounting position Vertical

[In] rated current 16 A

permissible voltage 100...240 V

Max line current 20 A

Input current limits 20 A

Load capacity 3300 VA

Network frequency 50/60 Hz

Outlet type and quantity 14 IEC 60320 C13

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Environment

Product certifications	cUL listed UL listed
Ambient air temperature for operation	0...50 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	61.2 cm
Package 1 Width	10.7 cm
Package 1 Length	12.3 cm
Package 1 Weight	2.55 kg
SCC14	10731304327766

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 748 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 739 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
Halogen-free status	Product contains halogen above thresholds

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	45
End of life manual availability	End of Life Information
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



