

Specifications

Photo is representative

Eaton EATS30N

Eaton ATS rack PDU, 1U, Inputs Hardwired, 7.4 kW max, 30A, 200-240V, Output Hardwired

General specifications

PRODUCT NAME	Eaton ATS PDU
CATALOG NUMBER	EATS30N
UPC	743172069528
PRODUCT LENGTH/DEPTH	440 mm
PRODUCT HEIGHT	43 mm
PRODUCT WIDTH	390 mm
PRODUCT WEIGHT	5 kg
COMPLIANCES	CE Marked
CERTIFICATIONS	CE
MODEL CODE	Eaton ATS 30A Netpack



Powering Business Worldwide

Product specifications

SPECIAL FEATURES

- Provides power redundancy to IT equipment
- Alternative to expensive redundant power supplies available from networking equipment vendors
- Compact, 1U rack form factor
- Seamlessly switches from one power source to the other
- Network management

TYPE	ATS
FORM FACTOR	1U
OUTLET CONTROL	No

PACKAGE CONTENTS

- ATS
- Quickstart guide
- Safety instructions
- Accessories for rack installation

OPERATING TEMPERATURE	0° to 40°C (32° to 104°F)
MOUNTING DIRECTION	Horizontal
COLOR	Black
INPUT CONNECTION	Hardwired
WATTAGE	7.4 kW max
AMPERAGE RATING	30A
INPUT VOLTAGE	200-240V
PHASE	Single-phase
FREQUENCY RATING	50/60 Hz
OUTLETS	Hardwired
NUMBER OF OUTPUTS HARDWIRED	1
SNMP	Yes
ETHERNET INTERFACE	Yes
SERIAL INTERFACE	No
MASS CONFIGURATION	Yes
ELECTRICAL CONNECTION	Screwed terminal
EVALUATION	At distance
MOUNTING DIMENSION	43

Resources

BROCHURES

[Eaton UPS Services Quick Guide - EN](#)

[Eaton UPS and battery services - EN](#)

COMPLIANCE INFORMATION

[EU declaration of conformity Eaton ATS](#)

(METRICAL)	
MOUNTING DIMENSION (STANDARDIZED)	482.6 mm (19 inch)
SWITCHABLE	No
OVER VOLTAGE CATEGORY	2
FITTED WITH:	LED indication Mounting material Ampere Meter
COMMUNICATION	HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

