Specifications

Eaton EVBAFC20A

Eaton Basic G4 Rack PDU, 0U, 22.5U, C20 input, 3m cord, 1ph, 3.7kW, 16A, 200-240V, 24 outlets (12)C13, (12)C39

General specifications	
PRODUCT NAME	Eaton Rack PDU G4
CATALOG NUMBER	EVBAFC20A
EAN	3553340697265
PRODUCT LENGTH/DEPTH	1000 mm
PRODUCT HEIGHT	53 mm
PRODUCT WIDTH	52 mm
PRODUCT WEIGHT	2.15 kg
COMPLIANCES	CB LVD Directive RoHS Directive WEEE Directive Packaging Directive
CERTIFICATIONS	IEC 62368-1 EN IEC 63000 CE EAC UKCA Cm Ukr cTUVus
MODEL CODE	PDU G4 BA 0U C20 16A 1P 12xC13,12xC39

EAT·N

Powering Business Worldwide

Additional information

OPERATING TEMPERATURE	0° to 60°C (32° to 140°F)
ACCESSORIES	• Rack PDU • Rack mounting accessories • Quickstart guide • Safety Instructions
MATERIAL	Aluminium
COLOR	Black

Electrical input

INPUT CONNECTION	C20
WATTAGE	3.7 kW max
AMPERAGE RATING	16A
INPUT VOLTAGE	200-240V
PHASE	Single-phase
FREQUENCY RATING	50/60 Hz
CORD LENGTH	3m

Electrical output

OUTLETS	(12) C13, (12) C39
NUMBER OF OUTPUTS C13	12
NUMBER OF OUTPUTS C19	12
NUMBER OF OUTPUTS (OTHER)	12
NUMBER OF OUTLETS WITH EARTH PIN	24

Technology & communications

TYPE	Basic Rack PDU
OUTLET CONTROL	No
SPECIAL FEATURES	• Versatile C39 outlet supports C14 or C20 power cord plug • High retention outlets designed to securely fit standard power cords and support P-Lock power cords • Color-coded outlet banks and corresponding circuit breakers
ETHERNET INTERFACE	No
SERIAL INTERFACE	No
SNMP	No
COMMUNICATION	No
MASS CONFIGURATION	No

Resources

BROCHURES	[Rack PDU G4 Brochure EN](#)
DECLARATIONS OF CONFORMITY	[EU declaration of conformity Rack PDU G4](#)

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	