

Product datasheet

Specifications



APC Smart-UPS SRT 10000VA 230V

SRT10KXLI

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase 380 V AC 3 phases 400 V AC 3 phases 415 V AC 3 phases
Input voltage	220 V 240 V 380 V 415 V
Input voltage limits	100...275 V adjustable (half load) 173...476 V adjustable (half load)
Number of input connectors	1 hard wire 3-wire (1P + N + E) 1 hard wire 5-wire (3P + N + E)
Network frequency	40...70 Hz auto-sensing
Output voltage	230 V 1 phase
Output voltage	220 V 240 V
Rated power in W	10000 W
rated power in VA	10000 VA
Output connection type	6 IEC 60320 C13 3 IEC Jumpers 4 IEC 60320 C19
Output connector type	Hard wire 3-wire (H N + E) for 1 zone(s)
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	Less than 2 %
Maximum configurable power in VA	10000 VA
Maximum configurable power in W	10000 W
UPS type	On-Line
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	APCRBC140

Graphs

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

Run Time	View Runtime Graph 
Efficiency	View Efficiency Graph 

Complementary

Battery type	Lead-acid internal included
Emergency power off	Yes
Free slots	1
Preinstalled device	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
UPS connectivity	Serial port USB port Embedded network management card 3 Available expansion slot
Surge energy rate	480 J
Colour	Black
Height	432 mm
Width	263 mm
Depth	715 mm
Product weight	111.82 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Mounting mode	Tower with included kit
Provided equipment	CD with software Documentation CD Installation guide Temperature probe USB cable Warranty card Web/SNMP management card
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	High density
Redundant	No
Range of product	Smart-UPS On-Line
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE EAC IRAM RCM VDE
Marking	CE Mark

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
IP degree of protection	IP20
Relative humidity	0...95 %
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	55 dBA
Heat dissipation	1947 Btu/h
Operating altitude	0...10000 ft

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	+/- 192 V (split battery referenced to neutral)
Extended runtime	1
Number of battery filled slots	0
Battery recharge time	1.5 h
Number of battery replacement quantity	2
Battery life	3...5 year(s)
Battery charger power	876 W rated

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46.100 cm
Package 1 Width	100.000 cm
Package 1 Length	60.000 cm
Package 1 Weight	126.820 kg

Contractual warranty

Warranty (in months)	36 UPS 24 Battery
-----------------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	21 597 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 613 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	18 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	19 950 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	16 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	409c68a1-39a6-4e5f-b080-12befe783ad8
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	65
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



