

Product datasheet

Specifications



APC Smart-UPS SRT 96V 3kVA RM Battery Pack



SRT96RMBP

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|--|
| Product or component type | External battery pack |
| Number of rack unit | 2U |
| Battery type | Lead-acid battery |
| Provided equipment | Rack mounting brackets User manual Warranty card |
| Range of product | Smart-UPS Battery Systems |
| Replacement battery | APCRBC152 |

Batteries & Runtime

| | |
|--|---------------------------|
| Number of battery free slots | 0 |
| Number of battery filled slots | 0 |
| Device mounting | Stand alone battery stack |
| Battery voltage | 96 V |
| Number of battery replacement quantity | 2 |

Physical

| | |
|--------------------|--------------|
| Colour | Black |
| Height | 85 mm |
| Width | 432 mm |
| Depth | 594 mm |
| Product weight | 40.6 kg |
| Mounting mode | Rack-mounted |
| Two post mountable | 1 |

Output

| | |
|------------------|-------|
| Battery capacity | 19 Ah |
|------------------|-------|

Conformance

| | |
|-----------|-------|
| Standards | OSHPD |
|-----------|-------|

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Operating altitude | 0...10000 ft |
| Relative humidity | 0...95 % non-condensing |
| Ambient air temperature for storage | -15...45 °C |
| Storage altitude | 0...15240 m |
| Storage Relative Humidity | 0...95 % non-condensing |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 23.9 cm |
| Package 1 Width | 59.9 cm |
| Package 1 Length | 83.1 cm |
| Package 1 Weight | 44.500 kg |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

| | |
|--|----------------|
| Total lifecycle Carbon footprint | 204 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 165 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 11 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 13 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 155 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 16 kg CO2 eq. |

Use Better

Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| SCIP Number | 488c31fb-3af8-42cf-9558-1362d000a07e |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |

Use Longer

Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again

Repack and remanufacture

| | |
|---------------------------------|---|
| Recyclability potential, in % | 48 |
| End of life manual availability | End of Life Information |
| Removable battery | User replaceable |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Image of product / Alternate images

Alternative

