

# Specifications

Photo is representative

## Eaton EFLX8F

Eaton FlexPDU, 1U, C20 input, 4 kW, 16A, 200-240V, Outlets: (1) C19/(8) FRENCH

### General specifications

<b>PRODUCT NAME</b>	Eaton Flex Rack PDU
<b>CATALOG NUMBER</b>	EFLX8F
<b>EAN</b>	3553340684241
<b>PRODUCT LENGTH/DEPTH</b>	80 mm
<b>PRODUCT HEIGHT</b>	44 mm
<b>PRODUCT WIDTH</b>	483 mm
<b>PRODUCT WEIGHT</b>	1.6 kg
<b>COMPLIANCES</b>	CE Marked
<b>CERTIFICATIONS</b>	CE
<b>MODEL CODE</b>	EATON FLEXPDU 8 FR



Powering Business Worldwide

## Additional specifications

**FORM FACTOR** 1U

**OUTLET CONTROL** No

### PACKAGE CONTENTS

- Rack PDU
- Mounting accessories
- Quickstart guide
- Safety Instructions

**OPERATING TEMPERATURE** 0° to 60°C (32° to 140°F)

## Electrical input

**INPUT CONNECTION** C20

**WATTAGE** 3.84 kW max

**AMPERAGE RATING** 16A

**INPUT VOLTAGE** 200-240V

**FREQUENCY RATING** 50/60 Hz

**CORD LENGTH** 2m

**PHASE** Single-phase

## Additional specifications

**ELECTRICAL CONNECTION** Socket outlet

**MOUNTING DIMENSION (METRICAL)** 44

**OVER VOLTAGE CATEGORY** 2

**MOUNTING DIMENSION (STANDARDIZED)** 482.6 mm (19 inch)

**SWITCHABLE** No

## Physical

**MOUNTING DIRECTION** Horizontal

**COLOR** Black

## Communications

**ETHERNET INTERFACE** No

**MASS CONFIGURATION** No

**SNMP** No

**SERIAL INTERFACE** No

## Resources

	<a href="#">Eaton ePDU G3 - Brochure</a>
	<a href="#">Eaton FlexPDU and Eaton HotSwap MBP - Datasheet</a>
BROCHURES	<a href="#">Eaton UPS Services Quick Guide - EN</a>
	<a href="#">Eaton UPS and battery services - EN</a>
COMPLIANCE INFORMATION	<a href="#">EU declaration of conformity Eaton FlexPDU and Eaton Hot-Swap MBP</a>
MANUALS AND USER GUIDES	<a href="#">Eaton Flex PDU - Installation and user manual (multiple languages)</a>

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

