

Product datasheet

Specifications



APC Smart-UPS RT 3000VA 230V - Marine



SURTD3000XLIM

Overview

Presentation High density, double-conversion on-line power protection with scalable runtime.

Main

Main Input Voltage	230 V
Input voltage	220 V 240 V
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Input voltage limits	180...270 V
Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Output voltage	230 V
Output voltage	220 V 240 V
Rated power in W	2100 W
Rated power in VA	3000 VA
Output connection type	8 IEC 60320 2 IEC Jumpers 2 IEC 60320
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1
Harmonic distortion	Less than 3 %
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2100 W
UPS type	On-Line
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Replacement battery	APCRBC140

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Emergency power off	Yes
Free slots	0
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge energy rate	555 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
Number of rack unit	3U
Cable length	2.4 m
Number of cables	1
Colour	Black
Height	432 mm
Width	130 mm
Depth	660 mm
Product weight	54.55 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No
Provided equipment	CD with software Relay board Smart UPS signalling RS-232 cable User manual
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certifications	CE DNV KCC
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...55 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...15240 m
IP degree of protection	IP20
Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	55 dBA
Heat dissipation	609 Btu/h

Operating altitude	0...10000 ft
--------------------	--------------

Batteries & Runtime

Battery type	Lead-acid battery
--------------	-------------------

Extended runtime	1
------------------	---

Number of battery filled slots	2
--------------------------------	---

Battery recharge time	2.5 h
-----------------------	-------

Number of battery replacement quantity	1
--	---

Battery life	3...5 year(s)
--------------	---------------

Battery charger power	359 W rated
-----------------------	-------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Height	34.7 cm
------------------	---------

Package 1 Width	60.3 cm
-----------------	---------

Package 1 Length	98 cm
------------------	-------

Package 1 Weight	63.64 kg
------------------	----------

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	4 342 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 356 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	16 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 960 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	4282bd22-a353-4f82-bb5c-97bbd7f1d1e9
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	58
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

