

Product datasheet

Specifications



Easy PDU, Basic, Zero U, 22 kW, 230V, (30) C13 & (12) C19 ; IEC309

EPDU1232B

⚠ Discontinued on: 17 Nov 2025

⚠ To be end-of-service on: 30 Sept 2028

⚠ To be discontinued

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	1.9 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit Vertical mounting brackets

Complementary

Input Voltage	400 V 3 phases
Height	1794 mm
Width	62 mm
Output Voltage	230 V
Depth	44.4 mm
Product weight	5.14 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 3P + N + PE
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Input current limits	32 A
Load capacity	22000 VA
Network frequency	50/60 Hz
Outlet type and quantity	30 IEC 60320 C13 12 IEC 60320 C19

Environment

Product certifications	CE TÜV EAC RCM
------------------------	-------------------------

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.000 cm
Package 1 Width	16.000 cm
Package 1 Length	165.000 cm
Package 1 Weight	6.200 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	12
Package 2 Height	37.500 cm
Package 2 Width	120.000 cm
Package 2 Length	210.000 cm
Package 2 Weight	93.800 kg

Contractual warranty

Warranty (in months)	12
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	128 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	105 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	45
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins