

# Product datasheet

Specifications



APC Easy Rack PDU, Metered,  
0U, 3 Phase, 22kW, 230V, 32A, 18  
x C13 and 6 x C19 outlets,  
IEC60309 3P+N+PE inlet

EPDU1232M

⚠ To be discontinued

⚠ Discontinued on: 6 Jun 2025

⚠ To be end-of-service on: 31 Dec 2027

## Main

Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	1.98 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit Vertical mounting brackets

## Complementary

Input Voltage	400 V 3 phases
Height	1506 mm
Width	62 mm
Output Voltage	230 V
Depth	44.4 mm
Product weight	4.64 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 3P + N + PE
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Input current limits	32 A
Load capacity	22000 VA
Network frequency	50/60 Hz
Outlet type and quantity	18 IEC 60320 C13 6 IEC 60320 C19

## Environment

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

<b>Product certifications</b>	CE EAC RCM TÜV
<b>Ambient air temperature for operation</b>	-5...45 °C
<b>Relative humidity</b>	5...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient air temperature for storage</b>	-25...65 °C
<b>Storage Relative Humidity</b>	5...95 %
<b>Storage altitude</b>	0...15240 m

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	166 cm
<b>Package 1 Width</b>	11 cm
<b>Package 1 Length</b>	16 cm
<b>Package 1 Weight</b>	5.48 kg

## Contractual warranty

<b>Warranty (in months)</b>	12
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	3 206 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	54 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 149 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	780cb2d6-f852-4c3c-987f-e705629194ca
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---

